

PREMIUM RADIAL AGRICULTURAL TYRES FOR GLOBAL FARMING

Tyre Size	Tread Pattern		Rim Size	Tube Type	Inflated Dimensions(mm)		Max Load(kg)	Max. Inflation Pressure(kpa)	Load Versus Speed Index	RCI
	Tyre	TRA Code			OD	SW				
440/65R24	HR45	R1(R1W)	W14L	TL/TT	1182	441	2360	240	138A8	37
480/65R24	HR45	R1(R1W)	W15L	TL/TT	1234	479	2725	240	143A8	38
440/65R28	HR45	R1(R1W)	W14L	TL/TT	1283	441	2575	240	141A8	39
480/65R28	HR45	R1(R1W)	W15L	TL/TT	1335	479	2900	240	145A8	40
540/65R28	HR45	R1(R1W)	W18L	TL/TT	1413	550	3550	240	152A8	41
600/65R28	HR45	R1(R1W)	W18L	TL/TT	1491	591	4125	240	157A8	42
540/65R30	HR45	R1(R1W)	W18L	TL/TT	1464	550	3650	240	153A8	42
540/65R34	HR45	R1(R1W)	W18L	TL/TT	1566	550	3550	240	152A8	43
540/65R38	HR45	R1(R1W)	W18L	TL/TT	1667	550	3650	240	153A8	44
600/65R38	HR45	R1(R1W)	W18L	TL/TT	1745	591	4750	240	162A8	45
650/65R38	HR45	R1(R1W)	DW20B	TL/TT	1813	645	5600	160	160A8	46
650/65R42	HR45	R1(R1W)	DW20B	TL/TT	1913	645	5150	240	168A8	47
650/65R42	HR45	R1(R1W)	DW20B	TL/TT	1913	645	6000	320	170A8	47
320/70R24	HR45	R1(R1W)	W10	TL/TT	1094	319	1250	240	116A8	35
360/70R24	HR45	R1(R1W)	W12	TL/TT	1152	357	1360	240	119A8	36
380/70R24	HR45	R1(R1W)	W12	TL/TT	1190	380	1900	240	125A8	37
380/70R28	HR45	R1(R1W)	W12	TL/TT	1293	380	1750	240	127A8	38
420/70R24	HR45	R1(R1W)	W13	TL/TT	1248	418	1900	160	130A8	38
495/70R24	HR45	R1(R1W)	W16L	TL/TT	1304	499	3875	240	155G	40
420/70R28	HR45	R1(R1W)	W13	TL/TT	1349	418	2060	160	133A8	39
480/70R28	HR45	R1(R1W)	W15L	TL/TT	1421*	479	3450	320	151A8	40
480/70R30	HR45	R1(R1W)	W15L	TL/TT	1478	479	3550	320	152A8	41
480/70R34	HR45	R1(R1W)	W15L	TL/TT	1580	479	2725	160	143A8	43
480/70R34	HR45	R1(R1W)	W15L	TL/TT	1580	479	3000	160	146A8	43
480/70R34	HR45	R1(R1W)	W15L	TL/TT	1580	479	3000	200	146A8	43
480/70R34	HR45	R1(R1W)	W15L	TL/TT	1580	479	3875	320	155A8	43
520/70R38	HR45	R1(R1W)	W16L	TL/TT	1749	516	3350	160	150A8	44
580/70R38	HR45	R1(R1W)	W18L	TL/TT	1827	577	3875	240	155A8	45
710/70R38	HR45	R1(R1W)	DW23A	TL/TT	1959	716	7750	360	179A8	47
800/70R38	HR45	R1(R1W)	DW25A	TL/TT	2085	798	8250	240	181A8	48
710/70R42	HR45	R1(R1W)	DW23A	TL/TT	2061	716	7750	320	179A8	48
620/70R42	HR45	R1(R1W)	DW20B	TL/TT	1980	610	5300	240	166A8	47
620/70R46	HR45	R1(R1W)	DW20B	TL/TT	3036	625	4750	240	167A8	48
480/80R42	HR45	R1(R1W)	DW15A	TL/TT	1835	479	5300	360	150A8	46
480/80R46	HR45	R1(R1W)	DW15A	TL/TT	1936	479	4250	240	158A8	47
480/80R50	HR45	R1(R1W)	DW15A	TL/TT	2038	479	5150	320	165A8	48
480/80R50	HR45	R1(R1W)	DW15A	TL/TT	2038	479	6000	520	177A8	48
280/85R24	HR45	R1(R1W)	W9	TL/TT	1086	282	1215	160	115A8	/
320/85R24	HR45	R1(R1W)	W10	TL/TT	1154	319	1500	160	122A8	/
340/85R24	HR45	R1(R1W)	W11	TL/TT	1188	343	1650	160	125A8	/
380/85R24	HR45	R1(R1W)	W12	TL/TT	1256	380	1950	160	131A8	/
420/85R24	HR45	R1(R1W)	W13	TL/TT	1324	418	2300	160	137A8	/
280/85R28	HR45	R1(R1W)	W9	TL/TT	1187	282	1320	160	118A8	/
320/85R28	HR45	R1(R1W)	W10	TL/TT	1255	319	1600	160	124A8	/
340/85R28	HR45	R1(R1W)	W11	TL/TT	1289	343	1750	160	127A8	/
380/85R28	HR45	R1(R1W)	W12	TL/TT	1357	380	2060	160	133A8	40
420/85R28	HR45	R1(R1W)	W13	TL/TT	1425	418	2430	160	139A8	41
380/85R30	HR45	R1(R1W)	W12	TL/TT	1408	380	2180	160	135A8	41
420/85R30	HR45	R1(R1W)	W13	TL/TT	1475	418	2500	160	140A8	41
460/85R30	HR45	R1(R1W)	W14L	TL/TT	1544	455	2900	160	145A8	/
380/85R34	HR45	R1(R1W)	W12	TL/TT	1510	380	2650	240	142A8	/
420/85R34	HR45	R1(R1W)	W13	TL/TT	1578	418	2650	160	142A8	43
460/85R34	HR45	R1(R1W)	W14L	TL/TT	1646	455	3075	160	147A8	/
420/85R38	HR45	R1(R1W)	W13	TL/TT	1679	418	2800	160	144A8	/
460/85R38	HR45	R1(R1W)	W14L	TL/TT	1747	455	3250	160	149A8	45
520/85R38	HR45	R1(R1W)	DW16L	TL/TT	1849	516	3875	160	155A8	46
650/85R38	HR45	R1(R1W)	DW21	TL/TT	2071	645	7500	320	178A8	48
520/85R42	HR45	R1(R1W)	DW16L	TL/TT	1951	516	5150	240	162A8	47
520/85R42	HR45	R1(R1W)	DW16L	TL/TT	1951	516	5150	280	167A8	47
520/85R42	HR45	R1(R1W)	DW16L	TL/TT	1951	516	5600	320	169A8	47
520/85R42	HR45	R1(R1W)	DW16L	TL/TT	1951	516	5600	320	169D	47
520/85R46	HR45	R1(R1W)	DW16L	TL/TT	2052	516	6500	400	173A8	48
420/90R30	HR45	R1(R1W)	W13	TL/TT	1518	418	3075	240	147A8	42
380/90R46	HR45	R1(R1W)	W12	TL/TT	1852	380	4375	400	159A8	46
380/90R46	HR45	R1(R1W)	W12	TL/TT	1852	380	4375	440	173D	46
480/95R50	HR45	R1(R1W)	DW16B	TL/TT	2182	479	5450	240	167A8	49



AG45

- Designed in special radial tyre ply cord, providing dimensional stability and low heat-up performance
- Low-carbon economy solutions for the four-wheel drive, high horsepower tractors and combines.
- Extended tread pattern design protects carcass like an iron rampart.
- Good self-cleaning large lugs provide excellent traction performance in grip and skid resistance.
- Wear puncture-resistant and anti-aging compounds provide super long service life.
- Apply to agriculture, forestry tractors, harvesters and other logging skider.